

Models LCD-2R & LCD-2A

Liquid Coffee Dispenser



Model LCD-2R/LCD-2A



GRINDMASTER™
CORPORATION



GRINDMASTER™
CORPORATION

Models LCD-2R & LCD-2A

Features

- Tomlinson valve dispense handles for manual or portion control fill on 2 coffee products and hot water
- Operator portion override button for large volume dispenses
- Holds two ½ gal or two 1 gal B-I-Bs
- Sold out device for B-I-Bs can be changed out for use with cans
- Thermal electric cooled product compartment on LCD-2R
- Digital controls for setup and calibration
- 4.0 gallon boiler
- Dispense up to 320 8oz cups per hour (based on 55°F water inlet)

Simple Dispensing Procedure

1. Place a cup on the cup target of the drain tray.
2. Pull and hold handle for manual dispense (pull and release when in portion mode).
3. When in manual mode release handle when the cup is 2/3 full.
4. Remove your drink and enjoy!

Specifications

	Model LCD-2R (chilled)	Model LCD-2A (ambient)
Dispense Ratio	15:1 up to 50:1	15:1 up to 50:1
Flow Rate (ounces/second)	2.0 ounces	2.0 ounces
Water Connector*	3/8" male flare	3/8" male flare
Dimensions (H x W x D)	32.5" x 13" x 26"	31" x 13" x 26"
Ship Weight	105 lbs.	105 lbs.

* Connect to a 3/8" I.D. or larger supply line. A shut-off valve should be installed in the line before the unit.

Volts	Heaters Used	Amps	Tank Heater Watts	Total Brewing Capacity (assume 55°F inlet temp)	Cord Attached	Minutes to Heat to Set Temperature (55°F - 180°F)
120V / 1Ph	1	15	1650	5 gal/hour	No	50
208/240V / 1Ph	1	30	5000/6600	15/20 gal/hour	No	12/16

Specifications are subject to improvement or change without notice.



GRINDMASTER™
CORPORATION

Tel (502) 425-4776 • Fax (502) 425-4664 • 1-800-695-4500 (USA & Canada only)
4003 Collins Lane • Louisville, KY 40245 • USA

www.grindmaster.com • email: info@grindmaster.com